

## **NSF Product and Service Listings**

These NSF Official Listings are current as of **Thursday**, **January 03**, **2013** at 12:15 a.m. Eastern Time. Please contact NSF International to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information: http://www.nsf.org/Certified/PwsComponents/Listings.asp?Company=C0028348&Standard=061&

## NSF/ANSI STANDARD 61 Drinking Water System Components - Health Effects

NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. Click here for a list of <u>Abbreviations used in these Listings</u>.

## Square D Company

8001 Knightdale Boulevard Knightdale, NC 27545 United States 888-778-2733 919-266-3671 Visit this company's website

Facility: Apodaca/Nuevo Leon, Mexico

## **Mechanical Devices**

Trade Designation	Size	Water Contact Temp	Water Contact Material
Switches/Sensors 9013F(A)(B)(CC)(DDD)(E)[G]	[1]	CLD 23	MLTPL

- [1] The following configurations are Certified:
  - (A) Mechanism type
    - R Reverse action
    - S Standard adjustable differential
    - T Non-adjustable differential
    - Y Higher HP with adjustable differential
  - (B) Enclosure type
    - G NEMA1 General Purpose Electrical Enclosure
    - W NEMA3R Outdoor Electrical Enclosure
  - (CC) Fluid connection type
    - 1 1/8" NPSF internal threads
    - 2, 12, 22, 32, 42, 52, 62, 72, 82, 92 1/4" NPSF internal

```
3, 13, 23, 33, 43, 53, 63, 73, 83, 93 - 3/8" NPSF internal
4 - Narrow Differential
8, 18, 28, 38, 48, 58, 68, 78, 88, 98 - 1/4" Flare
9, 19, 29, 39, 49, 59, 89, 99 - 1/4" NPT external
10 - 1/4" Bayonet, barbed
20 - 90° Elbow, 1/4" bayonet

(DDD) - Pressure Regulation
J15 - J99

(E) - Pulsation plug
"P" or blank
```

[G] Product also Certified to NSF/ANSI 61, Annex G and is in compliance with California's

Health & Safety Code Section 116875 (commonly known as AB1953) and Vermont Act 193.

Weighted average lead content <=0.25%; Solder and flux lead content <=0.2%.

NOTE: NSF has not conducted production control audits at this facility. Product Listing is based on type testing [ISO/TEC Guide 2: 1996(E/F/R) 14.5]

Number of matching Manufacturers is 1 Number of matching Products is 1 Processing time was 0 seconds

- Search Listings
- News Room
- About NSF
- Careers
- NSF Mark
- Client Log-In
- Privacy Policy
- Site Map
- Request Info
- Contact Us
- Copyright © 2004 NSF International.